

What is claimed is:

1. A method of diagnosing the presence of pathology in a biological sample, comprising the step  
5 of:  
    identifying a region in the biological sample containing an extracellular material;  
    obtaining infrared absorbance spectral data from the region containing the extracellular material; and  
10 determining, from the infrared absorbance spectral data, whether an infrared spectral marker is found in the region containing the extracellular material, wherein finding the infrared spectral marker is indicative of presence of pathology in the biological  
15 sample.
2. A method as in claim 1, wherein the infrared spectral marker is a relative flat baseline of an infrared band at about  $1280\text{ cm}^{-1}$ .
- 20 3. A method as in claim 2, wherein the extracellular material is connective tissue.
4. A method as in claim 1, wherein the pathology  
25 to be diagnosed is carcinoma.
5. A method as in claim 1, wherein the biological sample is a breast biopsy sample, and wherein the

pathology to be diagnosed is breast cancer.

6. A method as in claim 2, wherein the step of determining includes calculating a slope of the baseline  
5 of the infrared absorbance spectral band at about 1280  $\text{cm}^{-1}$  from infrared absorbance spectral intensities of a first baseline point wavenumber adjacent and greater than 1280  $\text{cm}^{-1}$  and a second baseline point wavenumber adjacent and smaller than 1280  $\text{cm}^{-1}$ .

10

7. A method as in claim 6, wherein the step of obtaining infrared absorbance spectral data includes measuring the infrared absorbance spectral intensities at the first and second baseline point wavenumbers from  
15 the region containing the extracellular material.

8. A method as in claim 7, wherein the step of measuring the infrared absorbance spectral intensities includes detecting an infrared image of the biological  
20 sample at the first baseline point wavenumber and detecting an infrared image of the biological sample at the second baseline point wavenumber.

9. A method as in claim 8, wherein the steps of  
25 detecting the infrared images use a focal plane array detector having multiple pixels to detect infrared light from the biological sample.

PATENT # 6,936,660

[illegible]

10

15

20

25

14. A method as in claim 13, wherein the infrared absorbance peak associated with the extracellular material is at a wavenumber of about  $1340\text{ cm}^{-1}$ .

5        15. A method as in claim 14, including the step of calculating the corrected peak intensity from a measured peak intensity of the infrared absorbance peak and measured baseline intensities of the infrared absorbance peak.

10

16. A method as in claim 6, wherein the first and second baseline point wavenumbers are about  $1303\text{ cm}^{-1}$  and  $1264\text{ cm}^{-1}$ , respectively.

15        17. A system for diagnosing presence of pathology in a biological sample supported on a supporting surface generally reflecting infrared light and generally transmitting visible light, comprising:

an infrared source for generating an input infrared  
20 beam for illuminating the biological sample;

a focal-plane array detector having multiple detection pixels for detecting infrared images of the biological sample, the biological sample including a region containing extracellular material;

25        infrared optical elements for focusing infrared light reflected by the supporting surface and through the biological sample to the focal-plane array detector;  
and

a computer connected to the focal plane array detector for receiving infrared image data, the computer being programmed to determine from infrared image data for the region containing the extracellular material whether the extracellular material exhibits an infrared spectral marker indicative of presence of pathology in the biological sample.

18. A system as in claim 17, wherein the infrared spectral marker is a relative flat baseline of an infrared band at about  $1280\text{ cm}^{-1}$ , and wherein the computer is programmed to calculate a value of baseline slope of the infrared band at about  $1280\text{ cm}^{-1}$  from the infrared image data.

19. A system as in claim 18, wherein the infrared source is a Fourier transform infrared spectrometer.

20. A system as in claim 18, wherein the beam path includes a first and second narrow bandwidth filters for illuminating the biological sample with infrared light of a first and second filter wavelengths adjacent and above and below, respectively,  $1280\text{ cm}^{-1}$ .

21. A system as in claim 20, wherein the computer receives image data from the detector representing infrared images at the first and second filter wavelengths, and wherein the computer is programmed to

*(The page contains faint, illegible markings or bleed-through from the reverse side.)*

15

20

25

25. A macroscopic infrared imaging system for imaging a biological sample mounted on a supporting

